

RWS Group Ltd, of Europa House, Marsham Way, Gerrards Cross, Buckinghamshire, England, hereby declares that, to the best of its knowledge and belief, the following document, prepared by one of its translators competent in the art and conversant with the English and German languages, is a true and correct translation of the accompanying German Patent Application No. DE 102 45 930 A1 filed on 30 September 2002.

Signed this 29th day of July 2008

A handwritten signature in black ink, appearing to read 'C. E. Sitch', written in a cursive style.

C. E. SITCH

Managing Director - UK Translation Division

For and on behalf of RWS Group Ltd

Description

The present invention relates to an optoelectronic
5 component in accordance with the precharacterizing part
of patent claim 1 and to a component-based module in
accordance with the precharacterizing part of claim 17.

Radiation-emitting semiconductor components can be
10 arranged in a matrix in order to attain a high-
intensity overall module.

An arrangement of this type, referred to as an LED
module, is known from DE 10051159 A1. In this case, a
15 plurality of optoelectronic semiconductor arrangements
or semiconductor chips are mounted on a support which
is in turn arranged on a heat sink. Despite the
increasing packing density of the semiconductor
components, it is possible to dissipate the heat
20 produced. In this case, the heat produced must not
affect the electrical behavior of the semiconductor
component, however, or must affect it only
insignificantly. This practice reduces the efficiency
of the overall module on account of the absorption of
25 the radiation from adjacent semiconductor components,
however.

By placing the individual radiation-emitting
semiconductor components in a reflector, it is possible
30 to improve the module's radiation and directional
characteristics, since at least some of the radiation
emitted at the side of the individual semiconductor
components is reflected into the primary radiation
direction.

35

A module with a high level of efficiency and very good
directional characteristics can be assembled from
individual semiconductor components which are each
situated in an individual reflector. In this context,

however, it is difficult to obtain a high packing density for the semiconductor components together with the reflector in the overall module. The contact-connections between the semiconductor components stand
5 in the way of flexible connection and a high packing density.

The present invention is therefore based on the object of providing an optoelectronic component and a
10 component-based module which allow adjacent semiconductor components or optoelectronic semiconductor arrangements to be in close arrangement.

In particular, the object is based on providing a
15 semiconductor component having a contact-connection arrangement which allows the conduction of heat to be isolated from the conduction of electricity.

This object is achieved by means of the features of
20 claims 1 and 17. Further features of advantageous refinements and developments of the optoelectronic component are specified in the dependent claims 2 to 16 and 18.

25 The invention provides an optoelectronic component having a semiconductor arrangement which emits and/or receives electromagnetic radiation and which is arranged on a support which is thermally conductively connected to a heat sink. Bonding wires connect the
30 external electrical connections to the connections of the semiconductor arrangement. The external electrical connections are arranged in electrically insulated fashion on the heat sink at a distance from the support.

35 This has the advantage that the electrical conductive connections are largely decoupled from the conduction of heat. The thermal connection of a semiconductor

arrangement or chip on the heat sink by means of the support allows a large number of chips to be arranged closely on the heat sink and allows the heat to be dissipated. The electrical contact-connection between
5 the chips can be made flexibly using the connections insulated from the heat sink. In addition, compact reflective housings can be fitted on the external electrical connections, which reduces the space requirement for the component and allows high luminous
10 efficiency.

This practice has the advantage that the flow of electric current does not pass through the heat sink, which dissipates the heat produced during operation of
15 the semiconductor component.

It is advantageous if the support contains a support substrate and at least one electrically insulating layer arranged thereon. Alternatively, the support
20 material itself is an electrical insulation. In that case, the semiconductor arrangement does not need to be insulated from the support separately and may be arranged on a conductive substrate without producing a short circuit between them or with the heat sink.

25 The semiconductor arrangement and the electrically insulating layer may have an electrically conductive layer arranged between them which is connected to an external electrical connection. This is expedient particularly for a semiconductor arrangement on a
30 conductive substrate, because it is possible to route a connection for the semiconductor arrangement by means of a bonding wire via the electrically conductive layer.

35 It is particularly advantageous if the external electrical connections include conductor tracks on a printed circuit board. The printed circuit board

contains an insulating substrate with a conductor track and can therefore be mounted directly on the heat sink. It is also possible for a plurality of printed circuit boards to be arranged above one another, these then
5 also being insulated from one another.

Conductor tracks which can be connected to one another by means of plated-through holes on different printed circuit boards arranged above one another further
10 increase the flexibility of the connection of a large number of optoelectronic components.

Provision is advantageously made for the support substrate to have at least one material with good
15 thermal conductivity from the group comprising Si, diamond-coated Si, diamond, SiC, AlN and BN.

It is also advantageous if the electrically insulating layer comprises SiO_2 . This is particularly
20 advantageously the case when the support layer comprises silicon.

When there are a large number of components, these materials used in semiconductor technology reduce the
25 voltages among one another and with respect to the semiconductor chips themselves.

In one advantageous embodiment, the semiconductor arrangement is attached to the support by means of a
30 metal solder or a thermally and/or electrically conductive adhesive.

Good thermal conduction or dissipation of heat is obtained if the support is attached to the heat sink by
35 means of a metal solder or a thermally conductive adhesive.

Very good radiation of light becomes possible if the semiconductor arrangement and the support are arranged in a basic housing which has reflective properties.

- 5 The radiation of light can be adapted to suit the chip optimally and individually if the basic housing contains precisely one semiconductor arrangement. In that case, the external efficiency of the semiconductor component does not decrease on account of absorption of
10 an adjacent semiconductor arrangement within the cavity.

The optoelectronic component based on the invention has a cavity or cutout in the basic housing which (cavity
15 or cutout) contains the semiconductor arrangement which emits and/or receives electromagnetic radiation. Unlike in conventional optoelectronic components, the reflector is at least produced not just by reflective lateral faces of the cavity in the basic housing
20 itself, but rather at least partly by a reflective filling compound which the cavity contains. For this, the material and the quantity of filling compound are chosen such that, during and/or after filling, the adhesive force between the material of the filling
25 compound and the material of the lateral faces of the cavity causes the filling compound to rise up on these lateral faces and form a parabola-shaped surface. This filling compound surface facing the front of the housing serves as a reflective area for electromagnetic
30 radiation emitted and/or received by the semiconductor arrangement.

In other words, the cavity is partly filled with the filling compound, and the adhesive force between the
35 filling compound and the basic housing causes an essentially convex internal face of the filling compound (as seen from the semiconductor arrangement) to be automatically established in the cavity, since

the filling compound rises up on the lateral internal faces of the cavity of the basic housing. The filling compound's parabolic internal faces formed in this manner form the reflector for the semiconductor arrangement inserted into the cavity.

Even with very small openings in the cavities, these reflective areas can easily be produced in the cavity through suitable metering of the filling compound. As a result, the lateral walls of the housing and the filling compound behave like a single reflector, which further improves the light radiation power. In addition, the conductor tracks, wires and the like which the cavity contains are enveloped by the filling compound without impairing the manner of operation thereof.

Hence, even in the case of optoelectronic components with narrow openings in the cavity and/or complex semiconductor arrangement and wiring arrangements in the cavity, the inventive measure can be used to provide reflectors within the cavity and hence to increase the external efficiency of the components.

It is particularly advantageous if the basic housing is formed at an angle on the inner side which faces the semiconductor arrangement, so that the basic housing has a reflective area for a portion of the radiation emitted by the semiconductor arrangement.

The filling compound provided is preferably TiO_2 , or an epoxy resin filled with TiO_2 particles, or silicone.

In addition, the cavity of the housing is at least partly filled with a radiation-pervious encapsulation compound. This firstly makes it possible to protect the chip and its connections. In addition, with appropriate choice of chip and of encapsulation compound, it is

possible to produce components in different colors. By way of example, white-radiating components using a GaN-based chip and an encapsulation compound which contains YAG:Ce particles.

5

This encapsulation compound may advantageously contain epoxy resin or silicone. When using silicone, mechanical stresses in the semiconductor component or in a module comprising individual semiconductor components can be reduced to a high extent.

10

With particular advantage, the individual optoelectronic components can be arranged in the form of a matrix to form a module. For a plurality of optoelectronic components, a respective basic housing is provided in this case.

15

In one particularly preferred embodiment of the invention, the support's topmost layer facing the semiconductor arrangement is electrically conductive. Preferably, this electrically conductive layer essentially comprises a metal.

20

The conductor tracks for connecting the semiconductor chips allow the optoelectronic components to be connected to an adjacent component in a highly space-saving manner. No bonding wire is routed via the edge of the basic housing. The conductor tracks allow components to be connected in complex fashion. The conductor tracks may be situated in a printed circuit board (e.g. FR4, flexible printed circuit board) which has appropriate cutouts. The printed circuit board may be in multilayer form, which means that in addition to conductor tracks further functional elements may be present in a multilayer structure.

30

35

Further advantages and advantageous developments of the inventive optoelectronic component can be found in the

exemplary embodiments described below in conjunction with the figure.

The figure shows a schematic illustration of a sectional view of the exemplary embodiment.

In the case of the optoelectronic component 1 shown in the figure, a semiconductor arrangement 4 emitting and/or receiving electromagnetic radiation is arranged on a support 22. The support 22 is thermally conductively connected to a heat sink 12 made of copper, aluminum or molybdenum, for example. External electrical connections 9 are electrically connected to the semiconductor arrangement 4 or to an electrically conductive layer 13 via bonding wires 7. The electrically conductive layer 13 makes contact with the underside of the semiconductor arrangement 4, which is constructed such that a current can flow vertically through the arrangement, e.g. by virtue of the substrate being conducted for the active layer which produces the light.

In another embodiment with an insulating substrate for the active layer, the second bonding wire is likewise routed to the semiconductor chip directly.

In the figure, the electrically conductive layer 13 is insulated from the support substrate 2 of the support 22 by means of an electrically insulating layer 14. The electrically insulating layer 14 may preferably have two layers and be made of silicon oxide and a passivation layer applied above that, e.g. made of silicon nitride, which electrically isolates the support substrate, which has good thermal conductivity and is preferably made of silicon or of gallium arsenide, from the electrically conductive layer 13. Ceramic-type materials with good thermal conductivity, such as aluminum nitride or boron nitride or carbides,

are also suitable as support substrate. The support 22 is mounted directly on a heat sink 12 made of aluminum, copper or molybdenum by means of a solder connection or an adhesive bond.

5

Likewise directly on the heat sink 12, external electrical connections 9 are arranged in electrically insulated fashion and at a distance from the support 22. The external electrical connections 9 are preferably conductor tracks from printed circuit boards 10 which are arranged above one another and which form the connection arrangement 8. The two chip connections require at least one printed circuit board. A plurality of chips in a module are preferably connected by 15 multilayer printed circuit boards which allow flexible connection. Different conductor tracks on various printed circuit boards are connected by means of plated-through holes.

20 The semiconductor arrangement 4 with the support 22 is situated in a basic housing 20 with a cutout or cavity 3. The basic housing may be a frame which is mounted on the printed circuit boards 8 with the electrical connections 9. This allows a very compact design for 25 the inventive component 1. This also allows the inner side 17 of the basic housing 20 to be in the form of a reflector 30 in order to output as much and as directional light as possible from the component.

30 The semiconductor chip 4 and the lateral walls 17 of the cavity 3 have a filling between them which comprises a reflective filling compound 16 which, by way of example, is made of epoxy resin filled with TiO_2 particles, the proportion of TiO_2 in the filling 35 compound 16 being sufficient to increase the reflective power of the filling compound to a significant extent. The filling compound extends on the chip side to approximately the top edge of the support 22.

- 10 -

Preferably, the proportion of TiO_2 in the filling compound 16 is between approximately 10 and 50% by volume. Particles comprising zirconium dioxide, zinc oxide, barium sulfate, gallium nitride, aluminum oxide or a mixture of at least two of these are also suitable for use with an epoxy resin in the filling compound 16. What is important is that the difference in reflective index between the epoxy resin and the particles is sufficiently great for the reflectivity of the filling compound to rise.

As seen from the semiconductor chip 4, the filling compound surface which faces the front 21 of the basic housing 20 is convex and forms a reflective area at least for a portion of the radiation emitted and/or received at the side.

The free surface region of the semiconductor chip 4 which is situated above the filling compound is covered by a radiation-pervious encapsulation compound 6 and, by way of example, is in turn made of an epoxy resin or other suitable reaction resin.

As can be seen in the sectional view of the figure, the filling level of the filling compound 16 is low adjacent to the semiconductor chip 4, i.e. adjacent to the support 22. This means that the shape of the surface of the filling compound 16 opens essentially parabolically toward the front in conjunction with the surface 30 of the lateral wall of the housing 20. With a suitable choice of material and of metering for the filling compound, this shape is obtained automatically on account of the adhesive forces between the filling compound and the material of the housing frame 20. The convex inner faces of the filling compound 16 (as seen from the semiconductor chips 4) serve as reflector for the radiation which is emitted and/or received by the semiconductor chips 4 at the side.

The reflective power of the filling compound 16 with the TiO_2 proportion it contains is up to approximately 80%. In comparison with an optoelectronic component in
5 which the cavity is filled exclusively with a transparent filling compound, the optoelectronic component 1 of the present invention was able to be used to increase the external efficiency considerably.

10 To protect the semiconductor chips 4, the cavity 3 is filled entirely with a radiation-pervious, for example transparent, encapsulation compound 6 which envelops the semiconductor chip 4 and which is pervious to radiation for emission or reception by the
15 semiconductor chips 4. As in the conventional components, suitable filling compounds made of transparent artificial resins, such as epoxy resin, or made of polycarbonate may be used for this encapsulation compound 6, which is preferably
20 particularly in tune with the properties of the filling compound.

The above description of the invention using the exemplary embodiment is naturally not to be understood.
25 to mean a restriction of the invention thereto. Rather, the inventive concept set out in claims 1 and 17 can be applied for a large number of very different designs.

Patent claims

1. An optoelectronic component (1) having a semiconductor arrangement (4) which emits and/or receives electromagnetic radiation and which is arranged on a support (22) which is thermally conductively connected to a heat sink (12), and having external electrical connections (9) which are connected to the semiconductor arrangement (4),
characterized in that
the external electrical connections (9) are arranged in electrically insulated fashion on the heat sink (12) at a distance from the support (22).
2. The optoelectronic component as claimed in claim 1,
characterized in that
the support contains a support substrate (2) and at least one electrically insulating layer (14) arranged thereon.
3. The optoelectronic component as claimed in claim 1 or 2,
characterized in that
the semiconductor arrangement (4) and the electrically insulating layer (14) have an electrically conductive layer (13) arranged between them which is connected to one of the external electrical connections (9).
4. The optoelectronic component as claimed in one of claims 1 to 3,
characterized in that
the semiconductor arrangement contains a semiconductor chip.

5. The optoelectronic component as claimed in one of claims 1 to 4,
characterized in that
the external electrical connections (9) include
5 conductor tracks on a printed circuit board.
6. The optoelectronic component as claimed in one of claims 1 to 5,
characterized in that
10 conductor tracks on different printed circuit boards arranged above one another can be connected to one another by means of plated-through holes.
7. The optoelectronic component as claimed in one of claims 2 to 6,
15 characterized in that
the support substrate (2) has at least one material with good thermal conductivity from the group comprising Si, diamond-coated Si, diamond, SiC, AlN and BN.
20
8. The optoelectronic component as claimed in one of claims 2 to 7,
characterized in that
25 the electrically insulating layer (14) comprises SiO₂.
9. The optoelectronic component as claimed in one of claims 1 to 8,
30 characterized in that
the semiconductor arrangement (4) is attached to the support (22) by means of a metal solder or a thermally and/or electrically conductive adhesive.
- 35 10. The optoelectronic component as claimed in one of claims 1 to 9,
characterized in that

- 14 -

the support (22) is attached to the heat sink (12) by means of a metal solder or a thermally conductive adhesive.

5 11. The optoelectronic component as claimed in one of
claims 1 to 10,
characterized in that
the semiconductor arrangement and the support (22)
are arranged in the cavity (3) of a basic housing
10 (20).

12. The optoelectronic component as claimed in claim
11,
characterized in that
15 the cavity (3) of the basic housing (20) contains
precisely one semiconductor arrangement (4).

13. The optoelectronic component as claimed in claim
11 or 12,
20 characterized in that
the basic housing (20) is formed at an angle on
the inner side (17) which faces the semiconductor
arrangement (4), so that the basic housing (20)
has a reflective area for a portion of the
25 radiation emitted by the semiconductor
arrangement.

14. The optoelectronic component as claimed in one of
claims 11 to 13,
30 characterized in that
the cavity (3) between the semiconductor
arrangement (4) and lateral walls (17) of the
cavity contains a reflective filling compound (6)
which, as seen from the semiconductor arrangement
35 toward the front (21) of the basic housing (20),
has a concave surface (30) which forms a
reflective area for a portion of the radiation.

- 15 -

15. The optoelectronic component as claimed in one of claims 1 to 14, characterized in that the filling compound contains TiO_2 or an epoxy resin filled with TiO_2 particles.
16. The optoelectronic component as claimed in one of claims 1 to 15, characterized in that the semiconductor arrangement (4) is at least partly encapsulated by a radiation-pervious encapsulation compound (6).
17. A component-based module having a plurality of optoelectronic components as claimed in one of claims 1 to 16, characterized in that the individual optoelectronic components are arranged in the form of a matrix and at least some of them are connected in series.
18. The component-based module as claimed in claim 17, characterized in that a plurality of optoelectronic components each have a basic housing.

There follows one sheet of drawings

Title: Optoelectronic component and a module based thereon

Abstract: The invention proposes an optoelectronic component (1) having a semiconductor arrangement (4) which emits and/or receives electromagnetic radiation and which is arranged on a support (22) which is thermally conductively connected to a heat sink (12), and having external electrical connections (9) which are connected to the semiconductor arrangement (4), where the external electrical connections (9) are arranged in electrically insulated fashion on the heat sink (12) at a distance from the support (22). This results in an optimized component in terms of the dissipation of heat loss and the radiation of light and also in terms of making electrical contact and the packing density in modules.

